

AVSS

Description

Multi-grip dome head rivet – Stainless / Stainless

Optimal for applications requiring the corrosion resistance of stainless steel and the versatility of a multi-grip rivet. The wide grip range ensures one rivet is suitable for a wide range of applications.


MaterialBodyStainless SteelAISI 304MandrelStainless SteelAISI 434

Finish Body Natural

Mandrel Natural



Specifications



Dimensions

Part Code	Diameter	Grip Range	Hole Size	Α	В	С	D
				±0.2	±0.1	±0.05	±0.1
AVSS-0613	4.80 (3/16")	1.5 - 6.0	5.00	10.30	9.80	1.85	3.40
AVSS-0616	4.80 (3/16")	2.5 – 7.5	5.00	12.70	9.80	1.85	3.40

Shear Strength

Part Code	Stem in shear plane	Stem outside shear plane	Tensile Strength	
	kN	kN	kN	
AVSS-06**	6.472	N/A	5.001	

Dimensions and specifications are subject to change without notice. Check your distributor for the latest data sheet

As this data is based on multiple tests in various thicknesses we recommend testing the fastener in your application when an exact strength figure is required, or the load to be applied comes close to the published data

Profast Pty Ltd QLD Profast WA Pty Ltd P: +61 7 3265 2267 P: +61 8 9456 5537 F: +61 7 3265 2257 F: +61 8 9455 2659 E: salesQLD@profast.com.au
E: salesWA@profast.com.au

W: www.profast.com.au
W: www.profast.com.au