



Description


Hydro-pneumatic Riveting Tool with vacuum mandrel extraction

This solid reliable tool features a double acting hydro-pneumatic actuation resulting in a quick cycle time while maintaining a high traction force. Capacity is up to 1/4" (6.4mm) aluminium rivets or 3/16" (4.8mm) in all other rivets. The RAC180 model also features vacuum mandrel extraction as well as a mandrel container at the rear for spent mandrels. The RAC180 is the tool of choice for volume installers of 3/16" diameter rivets in any material.





Right Angle Nose assembly for special clearance applications



Specifications

Model	RAC180
Туре	Hydro-Pneumatic
Construction	ABS Plastic & Steel
Capacity	1/4" (Aluminium Only) 3/16" (all materials)
Weight	2.05kg
Traction Force	6 bar – 1100 kg

Dimensions and specifications are subject to change without notice. Check you distributor for the latest data sheet

As this data is based on multiple tests in various thicknesses we recommend testing the fastener in your application when an exact strength figure is required, or the load to be applied comes close to the published data

 Profast Pty Ltd QLD
 P: +61 7 3265 2267
 F: +61 7 3265 2257
 E: salesQLD@profast.com.au
 W: www.profast.com.au

 Profast WA Pty Ltd
 P: +61 8 9456 5537
 F: +61 8 9455 2659
 E: salesWA@profast.com.au
 W: www.profast.com.au