

**Description**


9.8mm (3/8") Orlock - Dome Head - Steel

Orlock is one of our highest strength structural rivets. The blindside upset is bulbed which helps spread the clamp force so that the joint material is not deformed. The bulbed tail also leaves a neat finish with minimal protrusion on the blind side. The dual locking grooves on the mandrel provide excellent resistance to vibration as well as impressive shear strength and weather resistance.



<b>Material</b>	Body:	Low Carbon Steel
	Mandrel:	Carbon Steel
<b>Finish</b>	Body:	Zinc Plated Cr VI free
	Mandrel:	Zinc Plated Cr VI free

**Specifications**



**Dimensions**

Part Code	Diameter	Grip Range	Hole Size +0.03	A ±0.2	B ±0.35	C ±0.25	D ±0.1
BLDRC-12145XG	9.80 (3/8")	3.0 – 6.0	10.00	14.50	19.50	4.20	6.00
BLDRC-12175XG	9.80 (3/8")	6.0 – 9.0	10.00	17.50	19.50	4.20	6.00
BLDRC-12205XG	9.80 (3/8")	9.0 – 12.0	10.00	20.50	19.50	4.20	6.00
BLDRC-12235XG	9.80 (3/8")	12.0 – 15.0	10.00	23.50	19.50	4.20	6.00

**Shear Strength**

Part Code	Stem in shear plane kN (nom)	Stem outside shear plane kN	Tensile Strength kN (nom)
BLDRC-12***	25.500	N/A	12.750

Dimensions and specifications are subject to change without notice. Check your distributor for the latest data sheet

As this data is based on multiple tests in various thicknesses we recommend testing the fastener in your application when an exact strength figure is required, or the load to be applied comes close to the published data