

SP90R


Description

Countersunk head Max Grip pin – Steel

Two-piece swage lock fastening system consisting of a pin and a collar. These fasteners are versatile due to their wide grip range, high speed assembly and high shear and tensile strengths. The fasteners offer high clamp up force and vibration resistance.



Specifications



Dimensions

Part Code	Diameter	Grip Range	Hole Size	Α	В	С	D
			-0.2	-0.2	Max	Max	Max
SP90R-0610	4.80 (3/16")	3.6 – 16.0	5.20	5.00	9.30	2.60	45.40
SP90R-0620	4.80 (3/16")	8.0 – 32.0	5.20	5.00	9.30	2.60	58.40
SP90R-0810	6.40 (1/4")	4.3 – 16.0	6.80	6.60	12.20	3.30	49.30
SP90R-0820	6.40 (1/4")	8.0 - 32.0	6.80	6.60	12.20	3.30	63.70

Part Code	Shear Strength	Tensile Strength	Clamp Force	
	KN	KN	KN	
SP90R-06**	7.500	7.300	4.000	
SP90R-08**	9.800	13.330	5.300	

The tensile strength and clamp shown may be lower in practice and are for guidance purposes only. Lockbolts with a surface coating (zinc, clear passivate) have approx. 15% less tensile strength than shown.

Dimensions and specifications are subject to change without notice. Check you distributor for the latest data sheet

As this data is based on multiple tests in various thicknesses we recommend testing the fastener in your application when an exact strength figure is required, or the load to be applied comes close to the published data

Profast Pty Ltd QLD Profast WA Pty Ltd P: +61 7 3265 2267 P: +61 8 9456 5537 F: +61 7 3265 2257 F: +61 8 9455 2659 E: salesQLD@profast.com.au
E: salesWA@profast.com.au

W: www.profast.com.au
W: www.profast.com.au