

**For all
Sizes.**



**Powerful.
Fast.
Reliable.**

Blind nut inserts M3 to M12
Blind stud inserts M4 to M8



Rivdom eVNG 2

RIVDOM® eVNG 2

Battery-powered setting tool for blind nut inserts and stud inserts

Rivdom eVNG 2

Rivdom eVNG 2 gets to grips. **Uncompromising.**

The new **HONSEL** battery nut insert tool now offers the ultimate solution for cordless settings of blind nut inserts and bolts. Oriented to the demands of industrial series production, Rivdom eVNG 2 offers a wide range of features and options.

Rivdom eVNG 2 can store settings for up to 99 different blind nut inserts and call these up within seconds.

Rivdom eVNG 2 has a patented gearbox with two brushless motors.

Rivdom eVNG 2 offers a tool-free quick release mechanism.

Rivdom eVNG 2 can be operated with either force or stroke control.

Innovative. Flexible. Unbound.



Comfort control



Lean housing form - only 71mm wide!



Optional integrated scanner



Proven ergonomics, short trigger stroke, RivdomPLUS charging technology



Also for the setting of blind stud inserts from M4 to M8



Screwing on is performed by pushing the blind nut inserts onto the threaded mandrel or by pressing the trigger with which the speed can also be variably controlled

Special accessories

We tailor our tools individually to your application and adapt the necessary accessories accordingly. With these application solutions, we reduce costs and optimise the setting result. Our customers appreciate **PROFAST** particularly for this service. This naturally also applies to the new Rivdom eVNG 2! Ask us about threaded mandrels with coarse, fine or UNC/UNF thread as well as extended nosepieces and threaded mandrels.

Innovative, Sturdy and Reliable

Comfortable processing of Blind nut inserts up to M12!



Hanger bracket for balancer

1.5" OLED control display with 5 buttons well known from the RivSmart battery riveter

SD card scanner

Extra slim front sleeve - only 25mm

Programmable unscrewing speed.

Automatic setting of the nosepiece.

Threaded mandrel with new quick-release mechanism.

Quick-start function thanks to multi-function trigger.

All-hand soft grip – ideal for all hand sizes.

LED-illuminated riveting point.

Emergency Mode

Belt clip or application plate

Various counters, Service and blocking functions

Additional status LED

Force or stroke control!
Depending on the fastener to be set and the application, the **Rivdom eVNG 2** can be operated with either force or stroke control via the menu of the control display.

For blind nut inserts and stud inserts with left and right-hand thread!

Rivdom eVNG 2 has a patented gear-box with two independently operated BLDC motors. This allows the system to be variably switched on and off during the return stroke.

The brushless DC motors developed by **HONSEL** guarantee a practically wear-free, very long life cycle. Low current consumption and reduced heat development increase the battery life and efficiency.

hl BÜRSTENLOS BRUSHLESS

RivdomPLUS 20V Li ion rechargeable battery with state-of-charge indicator.

Rivdom
Made by HONSEL

Rivdom eVNG 2

RIVDOM® eVNG 2

Battery-powered setting tool for blind nut inserts and stud inserts



L-BOXX®

Sturdy and flexible.

The innovative system packaging solution.

The new **HONSEL** L-Boxx is also compatible with the L-Boxxes from other manufacturers.



State-of-charge indicator on every battery.



4.0 Ah battery available as an accessory!



Quick-charger

Rivdomplus

Charging technology

Future-oriented battery management

The powerful **HONSEL** Li ion batteries are fully charged in **less than 30 minutes** - the **90 % charge is reached after only approx. 20 minutes** - so that the charging cycle is always shorter than the battery-consuming working time!

High quality electronic quick-charger with **automatic identification of the battery used**. 12 V, 16 V and 20 V batteries from the Rivdom family can be charged using the same charger.

TOOL-FREE MAINTENANCE

ERGONOMY and COMFORT



Outstanding ergonomics:

Rubberised universal handle for all hand sizes. Perfect housing geometry.



Maximum comfort thanks to rotation trigger with very low trigger force/short trigger stroke.



Quick-release mechanism No more than one open-jaw wrench for maintenance!



CE

kg 2.4 kg

STROKE 20 mm

CHARGE < 30 min.

POWER 25,000 N

	M3	M4	M5	M6	M8	M10	M12
Aluminium	optional	Aluminium					optional
Steel	optional	Steel					optional
Stainless Steel	optional	Stainless Steel					optional
Steel (with wrench)		Steel					

Profast Pty Ltd
2/30 Kingtel Place
Geebung Qld 4034
Australia

Ph: +61 7 3261 2267
Fax: +61 7 3261 2257
Email: salesqld@profast.com.au

Profast (WA) Pty Ltd
25C Baile Rd
Canning Vale WA 6155
Australia

Ph: +61 8 9456 5537
Fax: +61 8 9455 2659
Email: saleswa@profast.com.au